



插拔式连接器
 额定电流: 8 A
 额定电压: 300 V
 间距: 3.5mm/3.81 mm
 安装: 波峰焊

目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group | B | C | D |
|----------------------------------|-----|-------|-----|
| 额定电压 Rate Voltage [V] | 300 | - | 300 |
| 额定电流 Rated Current [A] | 8 | - | 8 |
| 接线范围 Wire Range [AWG] | | - | |
| 耐电压 Dielectric Voltage-Withstand | | 1.6KV | |

技术参数-IEC

| 过电压类别 Overvoltage Category | III | III | II |
|---|-----|-----|-----|
| 污染等级 Contamination Class | 3 | 2 | 2 |
| 额定电压 Rated Voltage [V] | 160 | 160 | 250 |
| 额定电流 Rated Current [A] | 7 | 7 | 7 |
| 额定冲击电压 Impulse withstand voltage [KV] | 2.5 | 2.5 | 2.5 |
| 导线截面积[硬/柔] Conductor cross section [mm ²] | | - | |


材料 Material

| | |
|-----------------------------|---------|
| 绝缘材料 Insulation Material | PA66 |
| 阻燃等级 Flame retardant rating | UL94V-0 |

| | |
|-------------------------------------|-----------------|
| 导体材料 Conductor Material | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated |
| 一般参数 Other Data | |
| 间距/极数 Pitch/Poles [mm]/[P] | 3.5 , 3.81/2-24 |
| 剥线长度 Stripping Length [mm] | - |
| 螺丝/扭矩 Screw/Torque(Max)[N.m] | - |
| 工作温度 Operating temperature [°C] | -40°C~+105°C |
| 焊锡温度 Soldering temperature | 260°C/5S |
| 引针尺寸 Pin dimensions [mm] | 0.8*0.8 |
| PCB板孔径 PCB Hole Diameter [mm] | Ø1.4 |

尺寸图

PCB开孔图



配件



WJ15EDGKDGB-3.5/3.81