



目录仅供参考，实际规格依产品工程图为准 版本1.0

材质及电镀 Material

|               |                          |
|---------------|--------------------------|
| 螺丝 Screws     | M4.0 Steel Ni plated     |
| 焊脚 Pin Header | Copper alloy , Sn plated |
| 塑件 Housing    | PA66 , UL94V-0           |

电气性能 Electrical

|                            |                             |                  |
|----------------------------|-----------------------------|------------------|
| 参考标准 Standard              | UL                          | IEC              |
| 额定电压 Rated voltage         | 600V                        | 630V             |
| 额定电流 Rated current         | 40A                         | 41A              |
| 使用线径 Wire range            | 18-10AWG                    | 6mm <sup>2</sup> |
| 接触电阻 Contact Resistance    | 20mΩ                        |                  |
| 绝缘电阻 Insulation resistance | 500MΩ/DC500V                |                  |
| 耐电压 Withstanding voltage   | AC1600V/1Min                |                  |
| 温度范围 Temp.range            | -40℃~+105℃                  |                  |
| 扭矩 Torque                  | 12.24Kgf.cm/1.2Nm/10.6Lb.in |                  |

一般参数 Other Data

|                            |           |
|----------------------------|-----------|
| 间距/极数 Pitch/Poles [mm]/[P] | 13.0/2-18 |
|----------------------------|-----------|

|                                 |                             |
|---------------------------------|-----------------------------|
| 工作温度 Operating temperature [°C] | -40°C~+105°C                |
| 扭矩 Torque                       | 12.24Kgf.cm/1.2Nm/10.6Lb.in |

尺寸图

## PCB开孔图

