



目录仅供参考，实际规格依产品工程图为准 版本1.0

## 技术数据-UL/CUL

| 等级 Use Group                     | B     | C | D   |
|----------------------------------|-------|---|-----|
| 额定电压 Rate Voltage [V]            | 300   | - | 300 |
| 额定电流 Rated Current [A]           | 15    | - | 10  |
| 接线范围 Wire Range [AWG]            | 28-12 |   |     |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV |   |     |

## 技术参数-IEC

|                                                       |          |     |     |
|-------------------------------------------------------|----------|-----|-----|
| 过电压类别 Overvoltage Category                            | III      | III | II  |
| 污染等级 Contamination Class                              | 3        | 2   | 2   |
| 额定电压 Rated Voltage [V]                                | 320      | 320 | 630 |
| 额定电流 Rated Current [A]                                | 12       | 12  | 12  |
| 额定冲击电压 Impulse withstand voltage [KV]                 | 6        | 6   | 6   |
| 导线截面积[硬/柔] Conductor cross section [mm <sup>2</sup> ] | 0.25-2.5 |     |     |

## 材料 Material


|                             |         |
|-----------------------------|---------|
| 绝缘材料 Insulation Material    | PA66    |
| 阻燃等级 Flame retardant rating | UL94V-0 |

|                                     |              |
|-------------------------------------|--------------|
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |


一般参数 Other Data

|                                 |                 |
|---------------------------------|-----------------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 7.5 , 7.62/2-24 |
| 剥线长度 Stripping Length [mm]      | 8-9             |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]    | /               |
| 工作温度 Operating temperature [°C] | -40~+105        |
| 焊锡温度 Soldering temperature      | /               |
| 引针尺寸 Pin dimensions [mm]        | /               |
| PCB板孔径 PCB Hole Diameter [mm]   | /               |


尺寸图



配件



WJ0601/0701-02XX



WJ0601/0701-04XX



WJ0601/0701-06XX



WJ0601/0701-08XX

WJ0605/0705-02XX

WJ0605/0705-04XX