




 目录仅供参考，实际规格依产品工程图为准 版本1.0

技术参数-UL (1059)

等级 Use Group	B	C	D
额定电压 Rated Voltage [V]	600	600	600
额定电流 Rated Current [A]	30	30	5
耐电压 Withstanding Voltage	2200V/1Min		
接线范围 Wire Range	24-10AWG		

技术参数-IEC(60947-7-1)

过电压类别 Overvoltage Category	III
污染等级 Contamination Class	3
额定电压 Rated Voltage	800V
额定电流 Rated Current	32A
额定冲击电压 Impulse withstand voltage	8KV

导线截面积 Conductor cross section

单芯 Soild	0.2-6mm²
柔性导线 Flexible	0.2-4mm²
柔性导线带冷压头 Flexible with ferrule	0.2-4mm²


材料 Material

绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated


一般参数 Other Data

长/高/厚 Length/Height/Thickness [mm]	55.9/35.2/6.2
连接点数 Connection Points	2
剥线长度 Stripping Length [mm]	10-12
导轨类型 Type of rail	DIN 35
螺丝/扭矩 Screw/Torque(Max)[N.m]	/
工作温度 Operating temperature [°C]	-40~+105


尺寸图



配件



FUVA4-XX



EB-35



DGS1-35x7.5W4.2x12




DGL2-35x7.5A



DGL2-35x7.5D



MUV4-10




EW-35



DGS1-35x7.5W5.2x15



DGL2-35x7.5B




PUV4-80



DUV4-102



DGS1-35x7.5W



DGL2-35x7.5C