




目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

|                                  |       |     |     |
|----------------------------------|-------|-----|-----|
| 等级 Use Group                     | B     | C   | D   |
| 额定电压 Rate Voltage [V]            | 300   | 300 | 600 |
| 额定电流 Rated Current [A]           | 10    | 10  | 5   |
| 接线范围 Wire Range [AWG]            | 28-16 |     |     |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV |     |     |

技术参数-IEC

|                                          |         |     |    |
|------------------------------------------|---------|-----|----|
| 过电压类别 Overvoltage Category               | III     | III | II |
| 污染等级 Contamination Class                 | 3       | 2   | 2  |
| 额定电压 Rated Voltage [V]                   | 400     | -   | -  |
| 额定电流 Rated Current [A]                   | 18      | -   | -  |
| 额定冲击电压 Impulse withstand voltage [KV]    | 6       | -   | -  |
| 导线截面积[硬/柔] Conductor cross section [mm²] | 0.2-1.5 |     |    |

材料 Material

|                             |         |
|-----------------------------|---------|
| 绝缘材料 Insulation Material    | PA66    |
| 阻燃等级 Flame relardant rating | UL94V-0 |

|                                     |              |
|-------------------------------------|--------------|
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |

一般参数 Other Data

|                                 |          |
|---------------------------------|----------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 8.0/2-24 |
| 剥线长度 Stripping Length [mm]      | 8-9      |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]    | /        |
| 工作温度 Operating temperature [°C] | -40~+105 |
| 焊锡温度 Soldering temperature      | /        |
| 引针尺寸 Pin dimensions [mm]        | /        |
| PCB板孔径 PCB Hole Diameter [mm]   | /        |

尺寸图

