



Rated current: 30A
Rated voltage: 600V
Use wire diameter: 22-10AWG
spacing:11.6mm



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	600	600	600
Rated Current [A]	30	30	5
Wire Range [AWG]	20-10		
Dielectric Voltage-Withstand	2.2KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	800	1000	1000
Rated Current [A]	41	41	41

Impulse withstand voltage [KV]	8	8	8
Conductor cross section [mm ²]	6.0		

Material

Insulation Material	PBT
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data

Pitch/Poles [mm]/[P]	11.6/3,5,7,9,11,13
Stripping Length [mm]	10-13
Screw/Torque(Max)[N.m]	M4/1.2
Operating temperature [°C]	-40 ~ +130
Soldering method	Wave soldering
Pin dimensions [mm]	1.0*2.5
PCB Hole Diameter [mm]	1.7*3.4

Dimensions

PCB hole diagram

