


Rated current: 10A

Rated voltage: 300V

Use wire diameter: 28-16AWG

spacing:5.0mm

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	50	300
Rated Current [A]	10	10	10
Wire Range [AWG]		28-16	
Dielectric Voltage-Withstand		1.6KV	

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	320	320	630
Rated Current [A]	10	10	10

Impulse withstand voltage [KV]	4	4	4
Conductor cross section [mm²]	0.2-1.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	5.0/02-12
Stripping Length [mm]	10-12
Screw/Torque(Max)[N.m]	-
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	0.4*0.8
PCB Hole Diameter [mm]	Ø1.2

Dimensions

PCB hole diagram


2.10
2.30
12.70
15.30
17.95(REF)
3.95
5.00
0.40
0.80
3.10
5.50
11.20
3.00
5.00(XX−1)
5.00XX+1.50


5.50
3.10
3.95
5.00
5.00(XX−1)
φ1.20
P.C.B. LAYOUT