




Rated current: 6A  
Rated voltage: 150V  
Use wire diameter: /  
spacing:2.54mm  
Install:

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

| Use Group                    | B     | C | D |
|------------------------------|-------|---|---|
| Rate Voltage [V]             | 150   | - | - |
| Rated Current [A]            | 6     | - | - |
| Wire Range [AWG]             | -     |   |   |
| Dielectric Voltage-Withstand | 1.3KV |   |   |

IEC

| Overvoltage Category | III | III | II  |
|----------------------|-----|-----|-----|
| Contamination Class  | 3   | 2   | 2   |
| Rated Voltage [V]    | 32  | 160 | 160 |
| Rated Current [A]    | 6   | 6   | 6   |

|                                            |     |     |     |
|--------------------------------------------|-----|-----|-----|
| Impulse withstand voltage [KV]             | 0.8 | 2.5 | 2.5 |
| Conductor cross section [mm <sup>2</sup> ] | -   |     |     |

## Material


|                              |                           |
|------------------------------|---------------------------|
| Insulation Material          | HIGH-TEMPERATURE PLASTICS |
| Flame retardant rating       | UL94V-0                   |
| Conductor Material           | Copper alloy              |
| Plating of conductor surface | Sn plated                 |

## Other Data

|                            |                  |
|----------------------------|------------------|
| Pitch/Poles [mm]/[P]       | 2.54/2*2-2*24    |
| Stripping Length [mm]      | -                |
| Screw/Torque(Max)[N.m]     | -                |
| Operating temperature [°C] | -40 ~ +130       |
| Soldering method           | Reflow Soldering |
| Pin dimensions [mm]        | 0.64*0.64        |
| PCB Hole Diameter [mm]     | Ø1.2             |

## Dimensions

## PCB hole diagram



## Accessories



WJ15KVH-2.54