




Rated current: 30A
Rated voltage: 300V
Use wire diameter: 30-10AWG
spacing:6.35mm
Install:

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	300	300
Rated Current [A]	30	30	10
Wire Range [AWG]	30 ~ 10		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	500	630	1000
Rated Current [A]	32	32	32

Impulse withstand voltage [KV]	6	6	6
Conductor cross section [mm ²]	0.2-6.0/0.2-4.0		

Material

Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data

Pitch/Poles [mm]/[P]	6.35/2-24
Stripping Length [mm]	8
Screw/Torque(Max)[N.m]	M3.5/0.8
Operating temperature [°C]	-40 ~ +105
Soldering method	Wave soldering
Pin dimensions [mm]	0.9*0.9
PCB Hole Diameter [mm]	Ø1.5

Dimensions

PCB hole diagram

