




Rated current: 52A  
Rated voltage: 300V  
Use wire diameter: 20-6AWG  
spacing:10.16mm  
Install: Wave soldering



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

| Use Group                    | B     | C   | D   |
|------------------------------|-------|-----|-----|
| Rate Voltage [V]             | 300   | 300 | 300 |
| Rated Current [A]            | 52    | 52  | 5   |
| Wire Range [AWG]             | 20~6  |     |     |
| Dielectric Voltage-Withstand | 2.2KV |     |     |

IEC

| Overvoltage Category | III | III  | II   |
|----------------------|-----|------|------|
| Contamination Class  | 3   | 2    | 2    |
| Rated Voltage [V]    | 630 | 1000 | 1000 |
| Rated Current [A]    | 57  | 57   | 57   |

|                                            |          |   |   |
|--------------------------------------------|----------|---|---|
| Impulse withstand voltage [KV]             | 8        | 8 | 8 |
| Conductor cross section [mm <sup>2</sup> ] | 2.5~10.0 |   |   |

## Material

|                              |              |
|------------------------------|--------------|
| Insulation Material          | PA66         |
| Flame retardant rating       | UL94V-0      |
| Conductor Material           | Copper alloy |
| Plating of conductor surface | Sn plated    |

## Other Data

|                            |                |
|----------------------------|----------------|
| Pitch/Poles [mm]/[P]       | 10.16/2-24     |
| Stripping Length [mm]      | 10             |
| Screw/Torque(Max)[N.m]     | M4/1.2         |
| Operating temperature [°C] | -40 ~ +105     |
| Soldering method           | Wave soldering |
| Pin dimensions [mm]        | 1.2*1.6        |
| PCB Hole Diameter [mm]     | Ø2.4           |

## Dimensions

## PCB hole diagram

