


Rated current: 10A

Rated voltage: 300V

Use wire diameter: 28-12AWG

spacing:7.5mm

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	10	-	10
Wire Range [AWG]	28-12		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	400	630	1000
Rated Current [A]	21	21	21

Impulse withstand voltage [KV]	6	6	6
Conductor cross section [mm²]	0.2-2.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	7.5/2*2-2*24
Stripping Length [mm]	5-6
Screw/Torque(Max)[N.m]	-
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	0.7*0.7
PCB Hole Diameter [mm]	Ø1.3

Dimensions

PCB hole diagram


7.50(XX-1)+6.00
26.50
15.00
4.10
21.00
□0.70
7.50
3.10
7.50(XX-1)


7.50(XX-1)
7.50
3.10
ø1.30
15.00
P.C.B. LAYOUT
4.10