


Rated current: 30A

Rated voltage: 300V

Use wire diameter: 24-10AWG

spacing:7.5mm

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	150	300
Rated Current [A]	30	10	10
Wire Range [AWG]		24-10	
Dielectric Voltage-Withstand		1.6KV	

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	500	630	1000
Rated Current [A]	41	41	41

Impulse withstand voltage [KV]	6	6	6
Conductor cross section [mm²]	0.2-6.0		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	7.5/01-16
Stripping Length [mm]	11-12
Screw/Torque(Max)[N.m]	-
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	1.4*1.0
PCB Hole Diameter [mm]	Ø2.2

Dimensions

PCB hole diagram


23.00
1.00
12.50
8.00
29.10
WITHOUT COVER
4.50
4.80
7.50
7.50(XX−1)
7.50XX+1.50
1.40


12.50
8.00
4.80
7.50
7.50(XX−1)
Ø2.20
P.C.B. LAYOUT