




额定电流: 15A
额定电压: 300V
使用线径: 26-14AWG



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL (1059)

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	300	600
额定电流 Rated Current [A]	15	15	5
接线范围 Wire Range [AWG]	26 ~ 14		

技术参数-IEC (60947-7-1)

额定电压 Rated Voltage [V]	500
额定电流 Rated Current [A]	16
单芯 Solid [mm²]	0.2-1.5
柔性导线 Flexible [mm²]	0.2-1.5
柔性导线带冷压头 Flexible with ferrule [mm²]	0.2-1.0
过电压类别 Overvoltage Category	III

污染等级 Contamination Class	3
额定冲击电压 Impulse withstand voltage [KV]	6


材料 Material

绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated


一般参数 Other Date

长/高/厚 Length/Height/Thickness [mm]	65.6/41.1/3.5
剥线长度 Stripping Length [mm]	8-10

尺寸图




适配产品




FUVA1.5-XX



DUV1.5-202



PUV1.5-144




EB-35




EW-35



DGL2-35x7.5A



DGL2-35x7.5B



DGL2-35x7.5C



DGL2-35x7.5D