


使用线径: 20-6AWG



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL (1059)

等级 Use Group	B	C	D
接线范围 Wire Range [AWG]		20 ~ 6	

技术参数-IEC (60947-7-2)


单芯 Soild [mm²]	0.5-16.0
柔性导线 Flexible [mm²]	0.5-10.0
柔性导线带冷压头 Flexible with ferrule [mm²]	0.5-10.0
过电压类别 Overvoltage Category	III
污染等级 Contamination Class	3
额定冲击电压 Impulse withstand voltage [KV]	8

材料 Material

绝缘材料 Insulation Material	PA66
--------------------------	------

阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated
一般参数 Other Date	
长/高/厚 Length/Height/Thickness [mm]	67.9/49.7/10.2
剥线长度 Stripping Length [mm]	18

尺寸图




适配产品



DUV10-102




FUVA10-XX



MUV10-10



PUV10-48



EB-35




EW-35



DGL2-35x7.5A



DGL2-35x7.5B



DGL2-35x7.5C



DGL2-35x7.5D