




额定电流: 6A

额定电压: 150V

使用线径: /

间距:2.54mm

安装: 回流焊

目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group                     | B     | C | D |
|----------------------------------|-------|---|---|
| 额定电压 Rate Voltage [V]            | 150   | - | - |
| 额定电流 Rated Current [A]           | 6     | - | - |
| 接线范围 Wire Range [AWG]            | -     |   |   |
| 耐电压 Dielectric Voltage-Withstand | 1.3KV |   |   |

技术参数-IEC

|                                       |     |     |     |
|---------------------------------------|-----|-----|-----|
| 过电压类别 Overvoltage Category            | III | III | II  |
| 污染等级 Contamination Class              | 3   | 2   | 2   |
| 额定电压 Rated Voltage [V]                | 32  | 160 | 160 |
| 额定电流 Rated Current [A]                | 6   | 6   | 6   |
| 额定冲击电压 Impulse withstand voltage [KV] | 0.8 | 2.5 | 2.5 |

|                                          |   |
|------------------------------------------|---|
| 导线截面积[硬/柔] Conductor cross section [mm²] | - |
|------------------------------------------|---|

材料 Material

|                                     |                           |
|-------------------------------------|---------------------------|
| 绝缘材料 Insulation Material            | HIGH-TEMPERATURE PLASTICS |
| 阻燃等级 Flame relardant rating         | UL94V-0                   |
| 导体材料 Conductor Material             | Copper alloy              |
| 导体表面镀层 Plating of conductor surface | Sn plated                 |

一般参数 Other Date


|                                 |                  |
|---------------------------------|------------------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 2.54/2*2-2*24    |
| 剥线长度 Stripping Length [mm]      | -                |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]    | -                |
| 工作温度 Operating temperature [°C] | -40 ~ +130       |
| 焊接方式 Soldering method           | Reflow Soldering |
| 引针尺寸 Pin dimensions [mm]        | 0.64*0.64        |
| PCB板孔径 PCB Hole Diameter [mm]   | Ø1.2             |

尺寸图

PCB开孔图

## 插拔式接线端子

下载日期:2026-09-09



WJ15KVH-2.54