



贯通式接线端子

额定电流: 15A

额定电压: 300V

使用线径: -

间距:12.0mm

安装: 波峰焊接

目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group | B | C | D |
|----------------------------------|-----|-------|-----|
| 额定电压 Rate Voltage [V] | 300 | 300 | 300 |
| 额定电流 Rated Current [A] | 15 | 15 | 10 |
| 接线范围 Wire Range [AWG] | | - | |
| 耐电压 Dielectric Voltage-Withstand | | 1.6KV | |

技术参数-IEC

| 过电压类别 Overvoltage Category | III | III | II |
|---------------------------------------|-----|-----|------|
| 污染等级 Contamination Class | 3 | 2 | 2 |
| 额定电压 Rated Voltage [V] | 400 | 630 | 1000 |
| 额定电流 Rated Current [A] | 20 | 20 | 20 |
| 额定冲击电压 Impulse withstand voltage [KV] | 6 | 6 | 6 |

| | |
|---|---|
| 导线截面积[硬/柔] Conductor cross section [mm ²] | - |
|---|---|

材料 Material

| | |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material | PA66 |
| 阻燃等级 Flame retardant rating | UL94V-0 |
| 导体材料 Conductor Material | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated |

一般参数 Other Date

| | |
|---------------------------------|----------------|
| 间距/极数 Pitch/Poles [mm]/[P] | 12.0/1-12 |
| 焊接方式 Soldering method | Wave soldering |
| 引针尺寸 Pin dimensions [mm] | 0.8*2.8 |
| 工作温度 Operating temperature [°C] | -40 ~ +105 |
| PCB板孔径 PCB Hole Diameter [mm] | 3.0*1.0 |

尺寸图

PCB开孔图

