



固定式连接器

额定电流: 20A

额定电压: 300V

使用线径: 26-12AWG

间距:7.5mm

安装: 波峰焊



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group | B | C | D |
|----------------------------------|-------|-----|-----|
| 额定电压 Rate Voltage [V] | 300 | 150 | 300 |
| 额定电流 Rated Current [A] | 20 | 20 | 10 |
| 接线范围 Wire Range [AWG] | 26~12 | | |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV | | |

技术参数-IEC

| 过电压类别 Overvoltage Category | III | III | II |
|---------------------------------------|-----|-----|------|
| 污染等级 Contamination Class | 3 | 2 | 2 |
| 额定电压 Rated Voltage [V] | 500 | 630 | 1000 |
| 额定电流 Rated Current [A] | 24 | 24 | 24 |
| 额定冲击电压 Impulse withstand voltage [KV] | 6 | 6 | 6 |

| | |
|---|-----------------|
| 导线截面积[硬/柔] Conductor cross section [mm ²] | 0.2-4.0/0.2-2.5 |
|---|-----------------|

材料 Material

| | |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material | PA66 |
| 阻燃等级 Flame retardant rating | UL94V-0 |
| 导体材料 Conductor Material | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated |

一般参数 Other Data

| | |
|---------------------------------|----------------|
| 间距/极数 Pitch/Poles [mm]/[P] | 7.5/2-18 |
| 剥线长度 Stripping Length [mm] | 6-7 |
| 螺丝/扭矩 Screw/Torque(Max)[N.m] | M3/0.5 |
| 工作温度 Operating temperature [°C] | -40 ~ +105 |
| 焊接方式 Soldering method | Wave soldering |
| 引针尺寸 Pin dimensions [mm] | 0.8*1.0 |
| PCB板孔径 PCB Hole Diameter [mm] | Ø1.5 |

尺寸图

PCB开孔图

