

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。 本公司保留对涉及发明、实用新型和外观专利的所有权利。

1		2		3		4		5		6																																																																																																																																																												
								<table><tr><th colspan="5">REVISION RECORD</th></tr><tr><th>REV.</th><th colspan="2">DESCRIPTION</th><th>ECN No.</th><th>APPROVED</th><th>DATE</th></tr><tr><td>0</td><td colspan="2" rowspan="3">新发行</td><td></td><td>YaoFei</td><td>24.01.19</td></tr></table>		REVISION RECORD					REV.	DESCRIPTION		ECN No.	APPROVED	DATE	0	新发行			YaoFei	24.01.19	<table><tr><td colspan="5">UL/CUL 技术参数</td><td rowspan="2"></td></tr><tr><td colspan="6">UL/CUL Technical Data</td></tr><tr><td>等级</td><td colspan="2">Use Group</td><td>B</td><td>C</td><td>D</td></tr><tr><td>额定电压</td><td>Rated Voltage</td><td>[V]</td><td>300</td><td>-</td><td>300</td></tr><tr><td>额定电流</td><td>Rated Current</td><td>[A]</td><td>15</td><td>-</td><td>10</td></tr><tr><td>接线范围</td><td>Wire Range</td><td></td><td colspan="3" rowspan="2">-</td></tr><tr><td>单/多芯线</td><td>Solid/Stranded</td><td>[AWG]</td></tr><tr><td>耐电压</td><td>Withstanding Voltage</td><td></td><td colspan="3" rowspan="3">1600V/1Min</td></tr><tr><td colspan="6">IEC 技术参数</td></tr><tr><td colspan="6">IEC Technical Data</td></tr><tr><td>过电压类别</td><td>Overvoltage Category</td><td></td><td>III</td><td>III</td><td>II</td></tr><tr><td>污染等级</td><td>Contamination Class</td><td></td><td>3</td><td>2</td><td>2</td></tr><tr><td>额定电压</td><td>Rated Voltage</td><td>[V]</td><td>250</td><td>320</td><td>400</td></tr><tr><td>额定电流</td><td>Rated Current</td><td>[A]</td><td>10</td><td>10</td><td>10</td></tr><tr><td>额定冲击电压</td><td>Impulse withstand voltage</td><td>[KV]</td><td>4.0</td><td>4.0</td><td>4.0</td></tr><tr><td>导线截面积</td><td>Conductor cross section</td><td></td><td colspan="3" rowspan="3">-</td></tr><tr><td>硬质/柔性导线</td><td>Solid/ flexible</td><td>[mm²]</td></tr><tr><td colspan="6">一般参数 Other Data</td></tr><tr><td>间距</td><td>Pitch / 极数</td><td>Poles [mm] / [P]</td><td colspan="3">5.0 / 02~24</td></tr><tr><td>工作温度</td><td>Operating temperature</td><td>[°C]</td><td colspan="3">-40~105</td></tr><tr><td>焊锡温度</td><td>Soldering temperature</td><td></td><td colspan="3">260°C/5S</td></tr><tr><td>引针尺寸</td><td>Pin Dimensions</td><td>[mm]</td><td colspan="3">1.0*1.0</td></tr><tr><td>PCB板孔径</td><td>PCB Hole Diameter</td><td>[mm]</td><td colspan="3" rowspan="2">Ø1.7</td></tr><tr><td colspan="6">符合RoHS环保要求</td></tr></table>		UL/CUL 技术参数						UL/CUL Technical Data						等级	Use Group		B	C	D	额定电压	Rated Voltage	[V]	300	-	300	额定电流	Rated Current	[A]	15	-	10	接线范围	Wire Range		-			单/多芯线	Solid/Stranded	[AWG]	耐电压	Withstanding Voltage		1600V/1Min			IEC 技术参数						IEC Technical Data						过电压类别	Overvoltage Category		III	III	II	污染等级	Contamination Class		3	2	2	额定电压	Rated Voltage	[V]	250	320	400	额定电流	Rated Current	[A]	10	10	10	额定冲击电压	Impulse withstand voltage	[KV]	4.0	4.0	4.0	导线截面积	Conductor cross section		-			硬质/柔性导线	Solid/ flexible	[mm²]	一般参数 Other Data						间距	Pitch / 极数	Poles [mm] / [P]	5.0 / 02~24			工作温度	Operating temperature	[°C]	-40~105			焊锡温度	Soldering temperature		260°C/5S			引针尺寸	Pin Dimensions	[mm]	1.0*1.0			PCB板孔径	PCB Hole Diameter	[mm]	Ø1.7			符合RoHS环保要求					
REVISION RECORD																																																																																																																																																																						
REV.	DESCRIPTION		ECN No.	APPROVED	DATE																																																																																																																																																																	
0	新发行			YaoFei	24.01.19																																																																																																																																																																	
UL/CUL 技术参数																																																																																																																																																																						
UL/CUL Technical Data																																																																																																																																																																						
等级	Use Group		B	C	D																																																																																																																																																																	
额定电压	Rated Voltage	[V]	300	-	300																																																																																																																																																																	
额定电流	Rated Current	[A]	15	-	10																																																																																																																																																																	
接线范围	Wire Range		-																																																																																																																																																																			
单/多芯线	Solid/Stranded	[AWG]																																																																																																																																																																				
耐电压	Withstanding Voltage		1600V/1Min																																																																																																																																																																			
IEC 技术参数																																																																																																																																																																						
IEC Technical Data																																																																																																																																																																						
过电压类别	Overvoltage Category		III	III	II																																																																																																																																																																	
污染等级	Contamination Class		3	2	2																																																																																																																																																																	
额定电压	Rated Voltage	[V]	250	320	400																																																																																																																																																																	
额定电流	Rated Current	[A]	10	10	10																																																																																																																																																																	
额定冲击电压	Impulse withstand voltage	[KV]	4.0	4.0	4.0																																																																																																																																																																	
导线截面积	Conductor cross section		-																																																																																																																																																																			
硬质/柔性导线	Solid/ flexible	[mm²]																																																																																																																																																																				
一般参数 Other Data																																																																																																																																																																						
间距	Pitch / 极数	Poles [mm] / [P]	5.0 / 02~24																																																																																																																																																																			
工作温度	Operating temperature	[°C]	-40~105																																																																																																																																																																			
焊锡温度	Soldering temperature		260°C/5S																																																																																																																																																																			
引针尺寸	Pin Dimensions	[mm]	1.0*1.0																																																																																																																																																																			
PCB板孔径	PCB Hole Diameter	[mm]	Ø1.7																																																																																																																																																																			
符合RoHS环保要求																																																																																																																																																																						
<table><tr><th colspan="8">General Tolerances</th><th colspan="3">— ▯ ⊥</th></tr><tr><td>variable range</td><td>to 6</td><td>over 6 to 10</td><td>over 10 to 30</td><td>over 30 to 60</td><td>over 60 to 100</td><td>over 100 to 160</td><td>over 160 to</td><td>to 10</td><td>over 10 to 100</td><td>over 100 to</td></tr><tr><td>tolerance</td><td>±0.20</td><td>±0.30</td><td>±0.50</td><td>±0.70</td><td>±1.00</td><td>±1.30</td><td>±1.60</td><td>0.10</td><td>0.30</td><td>0.60</td></tr></table>		General Tolerances								— ▯ ⊥			variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to	tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60																																																																																																																																				
General Tolerances								— ▯ ⊥																																																																																																																																																														
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to																																																																																																																																																												
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60																																																																																																																																																												
1		2		3		4		5		6																																																																																																																																																												