





REVISION RECORD			
REV.	DESCRIPTION	ECN No.	APPROVED
V0		YUCZ	DATE
新发行			23.12.11



UL/CUL 技术参数			
UL/CUL Technical Data		cULus	
等级	Use Group	B	C D
额定电压	Rated Voltage	[V]	300 - 300
额定电流	Rated Current	[A]	15 - 10
接线范围	Wire Range		
单/多芯线	Solid/Stranded	[AWG]	-
耐电压	Withstanding Voltage	1600V/Min	

IEC 技术参数			
IEC Technical Data		IEC61984	
过电压类别	Overvoltage Category	III	III II
污染等级	Contamination Class	3	2 2
额定电压	Rated Voltage	[V]	250 320 630
额定电流	Rated Current	[A]	10 10 10
额定冲击电压	Impulse withstand voltage	[kV]	4.0 4.0 4.0
导线截面积	Conductor cross section		
硬质/柔性导线	Solid/flexible	[mm ²]	-

一般参数 Other Data			
间距	Pitch / 极数	Poles	[mm] / [P]
			5.0 / 2*02-2*24
工作温度	Operating temperature	[°C]	-40~105
焊接温度	Soldering temperature	260°C/5S	

符合RoHS环保要求			
2	Pin	Copper Alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	YUCZ	DATE	23.12.11	UNITS	mm	THIRD ANGLE PROJECTION	Φ
CHK.	YangHJ	DATE	23.12.11	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.12.11	SCALE	3:2	DRAWING TYPE: SP-03	REV V0

WANJI 慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD
PART NO.: WJ2EDGVH-5.0-2*XXP-1Y-00A

General Tolerances

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to
Tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。