





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除经许可外，复制或传播本文件内容，或未经许可擅自使用本文件内容，均属于侵权行为，本公司保留追究法律责任。 本公司保留对涉及发明、实用新型和外观设计的所有权利。



General Tolerances								— □ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

7	Spring	Stainless steel	/
6	Pin header3	Copper Alloy	Sn Plated
5	Pin header2	Copper Alloy	Sn Plated
4	Pin header1	Copper Alloy	Sn Plated
3	Cover	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

5					6				
REVISION RECORD									
REV.	ESCRPTION				ECN No.		APPROVED		DATE
V0	新发行						WuBW		24.06.24
UL/CUL 技术参数 UL/CUL Technical Data									
等 级		Use Group			B	C	D		
额定电压		Rated Voltage [V]			300	-	300		
额定电流		Rated Current [A]			10	-	10		
接线范围		Wire Range			28-12				
单/多芯线		Solid/Stranded [AWG]							
耐电压		Withstanding Voltage			1600V/1Min				
IEC 技术参数 IEC Technical Data					IEC60947-7-4				
过电压类别		Overvoltage Category			III	III	II		
污染等级		Contamination Class			3	2	2		
额定电压		Rated Voltage [V]			400	630	1000		
额定电流		Rated Current [A]			21	21	21		
额定冲击电压		Impulse withstand voltagea [KV]			6.0	6.0	6.0		
导线截面积		Conductor cross section			0.2~2.5				
硬质/柔性导线		Solid/ flexible [mm²]							
材 料					Material				
绝缘材料		Insulation Material			PA66				
阻燃等级		Imflammability			UL94V-0				
导体材料		Contactor Material			铜合金 Copper alloy				
导体表面镀层		Contactive Coating			镀锡 Sn Plated				
一般参数					Other Data				
间距		Pitch /极数		Poles [mm] / [P]	7.62/3*2~3*16				
工作温度		Operating temperatur [°C]			-40~105				
剥线长度		Stripping Length [mm]			5~6				
焊锡温度		Soldering temperature			260°C/5S				
引针尺寸		Pin Dimensions [mm]			0.7*0.7				
PCB板孔径		PCB Hole Diameter [mm]			Ø1.3				
S.	WuBW	DATE	24.06.24	UNITS	mm	THIRD ANGLE PROJECTION			
K.	HuHT	DATE	24.06.24	SIZE	A4	TYPE: CUSTOMER DRAWING			SHEET 1 of 1
P.	Jason	DATE	24.06.24	SCALE	2:1	DRAWING TYPE: SP-03			REV V0
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ245T3-7.62-3*XXP-1Y-00A			