





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除书给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。 本公司保留对专利及发明、实用新型和外观设计的所有权利。



General Tolerances

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	— □ ⊥		
								to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

4	Pin Header	Copper Alloy	Sn Plated
3	Cover	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

REVISION RECORD						
REV.	ESCRPTION			ECN No.	APPROVED	DATE
V0	新发行				ZhaoXY	24.01.23
UL/CUL 技术参数 UL/CUL Technical Data						
等 级		Use Group		B	C	D
额定电压		Rated Voltage [V]		300	-	300
额定电流		Rated Current [A]		15	-	10
接线范围		Wire Range		/		
单/多芯线		Solid/Stranded [AWG]				
耐电压		Withstanding Voltage		1600V/1Min		
IEC 技术参数 IEC Technical Data				IEC61984		
过电压类别		Overvoltage Category		III	III	II
污染等级		Contamination Class		3	2	2
额定电压		Rated Voltage [V]		320	320	630
额定电流		Rated Current [A]		12	12	10
额定冲击电压		Impulse withstand voltagea [KV]		4.0	4.0	4.0
导线截面积		Conductor cross section		/		
硬质/柔性导线		Solid/ flexible [mm²]				
材 料				Material		
绝缘材料		Insulation Material		PA66		
阻燃等级		Imflammability		UL94V-0		
导体材料		Contactor Material		铜合金 Copper alloy		
导体表面镀层		Contactive Coating		镀锡 Sn Plated		
一般参数				Other Data		
间距		Pitch /极数 Poles [mm] / [P]		5.0 / 02~24		
工作温度		Operating temperatur [°C]		-40~105		
焊锡温度		Soldering temperature		260°/5S		
引针尺寸		Pin Dimensions [mm]		0.6*1.0		
PCB板孔径		PCB Hole Diameter [mm]		Ø1.4		
ZhaoXY	DATE	24.01.23	UNITS	mm	THIRD ANGLE PROJECTION	
HuHT	DATE	24.01.23	SIZE	A4	TYPE: CUSTOMER DRAWING	
Jason	DATE	24.01.23	SCALE	2:1	DRAWING TYPE: SP-03	
					REV	V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD					PART NO.: WJ0405-03XX-1Y-00A	