




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经书面明确授权, 否则禁止转让、复制、利用、交流本文档的内容。侵犯者将承担赔偿责任。本公司保留所有权利及发明、实用新型和外观设计的所有权。



电气性能/Electrical
额定电压 /Rated voltage 300V
额定电流 /Rated current 15A
接触电阻 /Contact resistance 20mΩ
绝缘电阻 /Insulation resistance 500MΩ/DC500V
使用线径 /Wire range 22~14AWG
耐电压 /With standing voltage AC 1600V/1 Min
机械性能/Mechanica
扭矩/Torque 0.5Nm(4.5Lb.in)
温度范围 /Temp.Range -40°C~+105°C
瞬时温度 /MAX Soldering +260°C, for 5 Sec
尺寸/Dimensions
间距/Pitch 7.62mm
极数/Poles 2~20p

4	Cover	PC	UL94V-2
3	Pin Header	Copper Alloy	Sn Plated
2	Screws	Steel	M3 Steel Ni plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

General Tolerances								—	∇	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

DES.	ZhaoXY	DATE	24.04.01	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	HuHT	DATE	24.04.01	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	24.04.01	SCALE	2:1	DRAWING TYPE: SP-03	
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ28CM-XXP-1Y-00A	

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		ZhaoXY	24.04.01