



Contacts Pin 数	3Pin	4Pin	5Pin
B-Coding	 Male Female	 Male Female	 Male Female
Rated Current 额定电流	4A	4A	4A
Rated Voltage 额定电压	250V	250V	60V
PART NO.品名:	M12-B03-ST2-M02-BF1	M12-B04-ST2-M02-BF1	M12-B05-ST2-M02-BF1
Customized定制化:			

Wirelist

P1	P2
1	1
2	2
3	3
...	...
Shield	Shield



Panel cut-out

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
		IEC 技术参数 IEC61076-2-101		
		IEC Technical Data		
		工作温度 Operating temperatur [°C]		-25~+80
		防护等级 IP Class (IN Locked condition)		IP67
		额定电压 Rated Voltage [V]		
		额定电流 Rated Current [A]		
		导线截面积Conductor cross section		
		硬质/柔性导线 Solid/ flexible [mm²]		
		接线范围 Wire Range		
		单/多芯线 Solid/Stranded [AWG]		
		材 料 Material		
		绝缘材料 Insulation Material		PA 66
		阻燃等级 Imflammability		UL94V-0
		导体材料 Contactor Material		铜合金 Copper alloy
导体镀层 Contactive Coating		镀金 Gold Plated		
螺母/螺丝Connector Nut/Screw		Brass With Nickel Plated铜镀镍		
符合RoHS环保要求				

H	Resin	Black epoxy resin for sealing	g	2	
G	O-ring	O-ring,FKM Green	pcs	1	
F	NUT	NUT M16X1.5, Brass With Nickel Plated	pcs	1	
E	O-ring	O-ring,FKM Black	pcs	1	
D	Housing	B-Coding Female,Black PA66	pcs	1	
C	Housing	B-Coding Male,Black PA66	pcs	1	
B	Terminal	Terminal ,Brass With Gold Plated	pcs	X	
A	Screw	Screw M12 X1.0,Brass With Nickel Plated	pcs	1	
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

		慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD				PART NO.: M12-BXX-ST2-M02-BF1	
NO SPECIFIED TOLERANCE		Cus' P/N:		Order No :		Drawing No.:	SP-02-M0XXXX
LINEAR	0.5~6	±0.1	DES.	JUN	DATE	UNITS	mm
	6~30	±0.2	CHK.		DATE	SIZE	A4
	>30	±2%	APP.		DATE	SCALE	X:X
ANGLES	±1°				DATE	文件等级:外部公开	
						THIRD ANGLE PROJECTION	PAGE
							1 of 1