





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交还本文档的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。



Panel cut-out



# REVISION RECORD

| REV. | DESCRIPTION | ECN No. | APPROVED | DATE       |
|------|-------------|---------|----------|------------|
| V0   | --          |         |          | 2022.06.20 |

|                                   |                                |                                                                                     |  |   |
|-----------------------------------|--------------------------------|-------------------------------------------------------------------------------------|--|---|
| IEC 技术参数<br>IEC Technical Data    |                                | IEC61076-2-101                                                                      |  | A |
| 工作温度                              | Operating temperatur [°C]      | -25~+80                                                                             |  |   |
| 防护等级                              | IP Class (IN Locked condition) | IP67                                                                                |  |   |
| 额定电压                              | Rated Voltage [V]              | 250                                                                                 |  |   |
| 额定电流                              | Rated Current [A]              | 4                                                                                   |  |   |
| 导线截面积                             | Conductor cross section        |  |  |   |
| 硬质/柔性导线                           | Solid/ flexible [mm²]          |                                                                                     |  |   |
| 接线范围                              | Wire Range                     |  |  |   |
| 单/多芯线                             | Solid/Stranded [AWG]           |                                                                                     |  |   |
| 材 料                      Material |                                |                                                                                     |  |   |
| 绝缘材料                              | Insulation Material            | PA 66                                                                               |  |   |
| 阻燃等级                              | Imflammability                 | UL94V-0                                                                             |  |   |
| 导体材料                              | Contact Material               | 铜合金 Copper alloy                                                                    |  |   |
| 导体镀层                              | Contactive Coating             | 镀金 Gold Plated                                                                      |  |   |
| 螺母/螺丝                             | Connector Nut/Screw            | Brass With Nickel<br>Plated铜镀镍                                                      |  |   |
| 符合RoHS环保要求                        |                                |                                                                                     |  |   |

|                         |                     |
|-------------------------|---------------------|
| Contacts<br>Pin 数       | 4Pin                |
| D-Coding                |                     |
| Rated Current<br>额定电流   | 4A                  |
| Rated Voltage<br>额定电压   | 250V                |
| Wire Range<br>接线范围(AWG) | 22(Max)             |
| PART NO.品名:             | M12-D04-ST0-M02-BQ1 |

|           |                    |            |                                         |            |           |
|-----------|--------------------|------------|-----------------------------------------|------------|-----------|
| F         |                    | O-Ring     | O-Ring FKM Black                        | pcs        | 1         |
| E         |                    | Resin      | Black epoxy resin for sealing           | g          | 2         |
| D         |                    | Nut        | Nut:Brass With Nickel Plated            | pcs        | 1         |
| C         |                    | Housing    | D-Coding Male,Black PA66 UL94V-0        | pcs        | 1         |
| B         |                    | Terminal   | Male Terminal ,Brass With Gold Plated   | pcs        | X         |
| A         |                    | Screw      | Screw M12 X1.0,Brass With Nickel Plated | pcs        | 1         |
| 编号<br>No. | 料号<br>Materials.No | 品名<br>Name | 材 料 规 格<br>Description                  | 单位<br>Unit | 用量<br>Qty |

|                        |       |      |                                                                                                                                         |     |      |            |       |     |                                  |  |                                                                                       |
|------------------------|-------|------|-----------------------------------------------------------------------------------------------------------------------------------------|-----|------|------------|-------|-----|----------------------------------|--|---------------------------------------------------------------------------------------|
| NO SPECIFIED TOLERANCE |       |      | DES.                                                                                                                                    | PTQ | DATE | 2022.06.20 | UNITS | mm  | TYPE: CUSTOMER DRAWING           |  |  |
| LINEAR                 | 0.5~6 | ±0.1 | CHK.                                                                                                                                    |     | DATE |            | SIZE  | A4  | Drawing No.: SP-02-MXXXXXX       |  | SHEET 1 of 1                                                                          |
|                        | 6~30  | ±0.2 | APP.                                                                                                                                    |     | DATE |            | SCALE | 1:1 | Order No:                        |  | REV V0                                                                                |
|                        | >30   | ±2%  | <br>慈溪市万捷电子有限公司<br>CIXI WANJIE ELECTRONIC CO., LTD |     |      |            |       |     | PART NO.:<br>M12-D04-ST0-M02-BQ1 |  |                                                                                       |
| ANGLES                 | ±1°   |      |                                                                                                                                         |     |      |            |       |     |                                  |  |                                                                                       |