




Contacts Pin 数	5Pin
A—Coding	
Rated Current 额定电流	4A
Rated Voltage 额定电压	60V
Wire Range线范围	22AWG
PART NO. 品名: (1M)	M12-A05-ST2-F02-SCR-100N
PART NO. 品名: (2M)	M12-A05-ST2-F02-SCR-200N
PART NO. 品名: (3M)	M12-A05-ST2-F02-SCR-300N
PART NO. 品名: (5M)	M12-A05-ST2-F02-SCR-500N
Customized.定制化	

P1	Wirelist
1	brown
2	white
3	blue
4	black
5	grey
Shield	Braid

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度	Operating temperatur [°C]	-25~+80
防护等级	IP Class (IN Locked condition)	IP67
额定电压	Rated Voltage [V]	60
额定电流	Rated Current [A]	4
导线截面积	Conductor cross section	0.34
硬质/柔性导线	Solid/ flexible [mm²]	
接线范围	Wire Range	22
单/多芯线	Solid/Stranded [AWG]	
材料 Material		
绝缘材料	Insulation Material	PA 66
阻燃等级	Imflammability	UL94V-0
导体材料	Contactore Material	铜合金 Copper alloy
导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/Screw	Brass With Nickel Plated铜镀镍
符合RoHS环保要求		

G		Pipe	Shield Pipe,Brass With Nickel Plated	pcs	1
F		O—ring	O—ring,FKM Green	pcs	1
E		TPU	Molded With Black TPU	G	8
D		Housing	A—Coding Female 5PIN,Black PA66	pcs	1
C		Terminal	Female Terminal ,Brass With Gold Plated	pcs	5
B		Screw	Screw M12 X1.0,Stainless steel	pcs	1
A		Cable	UL TYPE 22AWG X5C+AL+Braid Black PUR Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

						慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD			PART NO.: M12-A05-ST2-F02-SCR-XXXX			
NO SPECIFIED TOLERANCE			Cus' P/N:		Order No.:		---		Drawing No.:		SP-02-MOXXXX	
LINEAR	0.5~6	±0.1	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION 		PAGE 1 of 1		
	6~30	±0.2										
	>30	±2%	CHK.	DATE	SIZE	A4						
ANGLES	±1°		APP.	DATE	SCALE	X:X		文件等级:外部公开				