


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文档的内容。侵犯者将承担赔偿责任。 本公司保留对涉及及发明、实用新型和外观设计的所有权利。




Contacts Pin 数	2Pin	3Pin	4Pin	5Pin
Coding 编码 A-Coding				
Rated Current 额定电流	13A	13A	13A	8A
Rated Voltage 额定电压	300V	300V	300V	300V
Wire Range接线范围	16AWG(1.5mm ²)	16AWG(1.5mm ²)	16AWG(1.5mm ²)	16AWG(1.5mm ²)
PART NO.品名: (0.15m)	M87-A02-ST0-M02-BQ1-015	M87-A03-ST0-M02-BQ1-015	M87-A04-ST0-M02-BQ1-015	M87-A05-ST0-M01-BQ1-015
PART NO.品名: (0.5m)	M87-A02-ST0-M02-BQ1-050	M87-A03-ST0-M02-BQ1-050	M87-A04-ST0-M02-BQ1-050	M87-A05-ST0-M01-BQ1-050
Customized.定制化:				

G		WIRE	WIRE: UL1015 18AWG PVC Jacket	pcs	X
F		NUT	NUT 7/8"–16UN, Brass With Nickel Plated	pcs	1
E		O–Ring	O–Ring FKM Black	pcs	1
D		Resin	Black epoxy resin for sealing	g	5
C		Housing	Housing Male,Black PA66	pcs	1
B		Terminal	Male Terminal ,Brass With Gold Plated	pcs	X
A		Screw	Screw ,Brass With Nickel Plated	pcs	1
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
T0	--			2023.05.16

IEC 技术参数		
IEC Technical Data		
工作温度	Operating temperatur [°C]	-25~+105
防护等级	IP Class (IN Locked condition)	IP67
额定电压	Rated Voltage [V]	_____
额定电流	Rated Current [A]	_____
导线截面积	Conductor cross section	1.0
硬质/柔性导线	Solid/ flexible [mm²]	
接线范围	Wire Range	
单/多芯线	Solid/Stranded [AWG]	
材料 Material		
绝缘材料	Insulation Material	PA 66
阻燃等级	Imflammability	UL94V-0
导体材料	Contactur Material	铜合金 Copper alloy
导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/Screw	Brass With Nickel Plated铜镀镍
符合RoHS环保要求		



Panel cut-out

NO SPECIFIED TOLERANCE		DES.	JUN	DATE	2023.05.16	UNITS	mm	TYPE: CUSTOMER DRAWING			
LINEAR	0.5~6	±0.1	CHK.		DATE		SIZE	A4	Drawing No.: SP-02-M00XXX	SHEET 1 of 2	
	6~30	±0.2	APP.		DATE		SCALE	1:1	Order No:XXXXXX	REV	T0
	>30	±2%	 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.:(see Table) M87-AXX-ST0-M02-BQ1-XXX		
ANGLES	±1°										

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交还本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

1

2

3



4

5

6

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
T0	--	/		2023.05.16



IEC 技术参数		
IEC Technical Data		
工作温度	Operating temperatur [°C]	-25~+105
防护等级	IP Class (IN Locked condition)	IP67
额定电压	Rated Voltage [V]	_____
额定电流	Rated Current [A]	_____
导线截面积	Conductor cross section	
硬质/柔性 导线	Solid/ flexible [mm²]	
接线范围	Wire Range	
单/多芯线	Solid/Stranded [AWG]	
材 料 Material		
绝缘材料	Insulation Material	PA 66
阻燃等级	Imflammability	UL94V-0
导体材料	Contactur Material	铜合金 Copper alloy
导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/Screw	镀金 With Nickel Plated铜镀镍
符合RoHS环保要求		

NO SPECIFIED TOLERANCE			DES.	PTQ	DATE		UNITS	mm	TYPE: CUSTOMER DRAWING		
LINEAR	0.5~6	±0.1	CHK.		DATE		SIZE	A4	Drawing No.: SP-02-M00XXX		SHEET 2 of 2
	6~30	±0.2	APP.		DATE		SCALE	1:1	Order No: XXXXXX		REV T0
	>30	±2%									
ANGLES	±1°					慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD			PART NO.: (see Table) M87-AXX-ST0-M02-BQ1-XXX		

1

2

3

4

5

FOR-0371 Rev.1.0