




Contacts Pin 数	8Pin
A—Coding	
Rated Current 额定电流	2A
Rated Voltage 额定电压	30V
Wire Range线范围	24AWG
PART NO. 品名: (1M)	M12-A08-ST0-M02-SCR-100N
PART NO. 品名: (2M)	M12-A08-ST0-M02-SCR-200N
PART NO. 品名: (3M)	M12-A08-ST0-M02-SCR-300N
PART NO. 品名: (5M)	M12-A08-ST0-M02-SCR-500N
Custiomized. 定制化	

P1	Wirelist
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度 Operating temperatur [°C]	-25~+80	
防护等级 IP Class (IN Locked condition)	IP67	
额定电压 Rated Voltage [V]	30	
额定电流 Rated Current [A]	2	
导线截面积Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]	0.25	
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]	24	
材 料 Material		
绝缘材料 Insulation Material	PA 66	
阻燃等级 Imflammability	UL94V-0	
导体材料 Contactor Material	铜合金 Copper alloy	
导体镀层 Contactive Coating	镀金 Gold Plated	
螺母/螺丝 Connector Nut/Screw	不锈钢 Stainless steel	
符合RoHS环保要求		

E		TPU	Molded With Black TPU	G	8
D		Housing	A-Coding Male 8PIN,Black PA66	pcs	1
C		Terminal	Male Terminal ,Brass With Gold Plated	pcs	8
B		Screw	Screw M12 X1.0,Stainless steel	pcs	1
A		Cable	UL TYPE 24AWG X8C Black PUR Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材 料 规 格 Description	单位 Unit	用量 Qty

		慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD				PART NO.: M12-A08-ST0-M02-SCR-XXXN	
NO SPECIFIED TOLERANCE		Cus' P/N:	Order No: ---		Drawing No.:	SP-02-M00XXX	
LINEAR	0.5-6	±0.1	DES.	JUN	DATE	UNITS	mm
	6-30	±0.2	CHK.	DATE	SIZE	A4	
	>30	±2%	APP.	DATE	SCALE	X:X	
ANGLES	±1°		DATE		SCALE	X:X	文件等级: 外部公开
						1 of 1	