



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度	Operating temperature [°C]	-25~+80
防护等级	IP Class (IN Locked condition)	IP67
额定电压	Rated Voltage [V]	
额定电流	Rated Current [A]	
导线截面积	Conductor cross section	
硬质/柔性导线	Solid/ flexible [mm²]	
接线范围	Wire Range	
单/多芯线	Solid/Stranded [AWG]	
材 料 Material		
绝缘材料	Insulation Material	PA 66
阻燃等级	Imflammability	UL94V-0
导体材料	Contactoer Material	铜合金 Copper alloy
导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/Screw	Brass With Nickel Plated铜镀镍
符合RoHS环保要求		

Contacts Pin 数	3Pin	4Pin	5Pin
B-Coding			
Rated Current 额定电流	4A	4A	4A
Rated Voltage 额定电压	250V	250V	60V
PART NO.品名:	M12-B03-ST2-M02-BF2	M12-B04-ST2-M02-BF2	M12-B05-ST2-M02-BF2
Customized定制化:			


Wirelist

P1

P2

1 ————— 1
2 ————— 2
3 ————— 3

Shield ————— Shield



Panel cut-out

H		Resin	Black epoxy resin for sealing	g	2
G		O-ring	O-ring,FKM Green	pcs	1
F		NUT	NUT PG9, Brass With Nickel Plated	pcs	1
E		O-ring	O-ring,FKM Black	pcs	1
D		Housing	B-Coding Female,Black PA66	pcs	1
C		Housing	B-Coding Male,Black PA66	pcs	1
B		Terminal	Terminal ,Brass With Gold Plated	pcs	X
A		Screw	Screw M12 X1.0,Brass With Nickel Plated	pcs	1
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD							PART NO.: M12-BXX-ST2-M02-BF2		
NO SPECIFIED TOLERANCE			Cus' P/N:	Order No.:		---		Drawing No.:	SP-02-M0XXXX
LINEAR	0.5-6	±0.1	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION	PAGE
	6~30	±0.2	CHK.		DATE	SIZE	A4		1 of 1
	>30	±2%							
ANGLES	±1°		APP.		DATE	SCALE	X:X	文件等级:外部公开	