





Contacts Pin 数	3Pin	4Pin	5Pin	8Pin	12Pin	17Pin
A-Coding						
Rated Current 额定电流	4A	4A	4A	2A	1.5A	1.5A
Rated Voltage 额定电压	250V	250V	60V	30V	30V	30V
Wire Range线范围	22AWG	22AWG	22AWG	24AWG	26AWG	26AWG
PART NO. 品名:	M12-A03-ST0-F02-BH2-050	M12-A04-ST0-F02-BH2-050	M12-A05-ST0-F02-BH2-050	M12-A08-ST0-F02-BH2-050	M12-A12-ST0-F02-BH2-050	M12-A17-ST0-F02-BH2-050
Customized定制化:						



 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD							PART NO.: M12-AXX-ST0-F02-BH2-050				
NO SPECIFIED TOLERANCE		Cus' P/N:	Order No :		---		Drawing No.:	SP-02-M00XXX			
LINEAR	0.5~6	±0.1	DES.	JUN	DATE		UNITS	mm	THIRD ANGLE PROJECTION		PAGE
	6~30	±0.2									
	>30	±2%	CHK.		DATE		SIZE	A4			
ANGLES	±1°		APP.		DATE		SCALE	X:X	文件等级:外部公开		

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

3Pin

P1	Wirelist
1	brown
3	blue
4	black

4Pin

P1	Wirelist
1	brown
2	white
3	blue
4	black

5Pin

P1	Wirelist
1	brown
2	white
3	blue
4	black
5	grey

17Pin

P1	Wirelist
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey/pink
12	red/blue
13	white/green
14	brown/green
15	white/yellow
16	yellow/brown
17	white/grey

12Pin

P1	Wirelist
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey/pink
12	red/blue

8Pin

P1	Wirelist
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD								PART NO.: M12-AXX-ST0-F02-BH2-050				
NO. SPECIFIED TOLERANCE			Cus' P/N:		Order No.:		---		Drawing No.:		SP-02-M000XX	
LINEAR	0.5~6	±0.1	DES.	Jun	DATE		UNITS	mm	THIRD ANGLE PROJECTION 	PAGE		
	6~30	±0.2	CHK.		DATE		SIZE	A4		2 of 2		
	>30	±2%	APP.		DATE		SCALE	X:X		文件等级: 外部公开		
ANGLES	±1°		APP.		DATE		SCALE	X:X	文件等级: 外部公开			